



Standard 24 PoE

[USW-24-POE](#)

Mechanical

Dimensions	442 x 200 x 44 mm (17.4 x 7.9 x 1.7")
-------------------	---------------------------------------

Weight	Without mounting brackets: 3 kg (6.6 lb) With mounting brackets: 3.1 kg (6.8 lb)
---------------	---

Enclosure material	SGCC steel
---------------------------	------------

Hardware

Management interface	Ethernet In-Band
-----------------------------	------------------

Networking interface	(24) GbE RJ45 ports (2) 1G SFP ports
-----------------------------	---

PoE interface	(16) PoE/PoE+ (Pins 1, 2+; 3, 6-)
----------------------	-----------------------------------

Total non-blocking throughput	26 Gbps
--------------------------------------	---------

Switching capacity	52 Gbps
---------------------------	---------

Forwarding rate	38.69 Mpps
------------------------	------------

Power method	Universal input, 100—240V AC, 50/60 Hz
---------------------	--

Power supply	AC/DC, internal, 120W
---------------------	-----------------------

Supported voltage range	100—240V AC
--------------------------------	-------------

Max. power consumption	25W (Excluding PoE output)
-------------------------------	----------------------------

Total available PoE	95W
----------------------------	-----

Max. PoE wattage per port by PSE	PoE+: 32W
---	-----------

Voltage range PoE mode	PoE: 44—57V
-------------------------------	-------------

	PoE+: 50—57V
--	--------------

ESD/EMP protection	Air: ± 16kV, contact: ± 12kV
---------------------------	------------------------------

LCM display	(1) 1.3" touchscreen
--------------------	----------------------

Button	Factory reset
---------------	---------------

Shock and vibration	ETSI300-019-1.4 Standard
----------------------------	--------------------------

Ambient operating temperature	-5 to 40° C (23 to 104° F)
--------------------------------------	----------------------------

Ambient operating humidity	10 to 90% noncondensing
-----------------------------------	-------------------------

Certifications	CE, FCC, IC
-----------------------	-------------

Switching Features

Layer 2 features	IGMP snooping STP / RSTP with priorities and port-level disable Port isolation Storm control Voice VLAN
-------------------------	---



Port mirroring
LACP port aggregation
Multicast / broadcast rate limiting
MAC address blocking
Flow control
802.1X control
Jumbo frames
Proprietary loop protection
DHCP snooping / guarding
Egress rate limit
LLDP-MED
Port restricted by MAC
Device isolation with ACLs

Layer 3 features

–

LEDs

System

Status

Ethernet

PoE

Speed/link/activity

SFP

Link/activity

Application Requirements

UniFi Network

Version 7.2.94 and later